

:
:
..

μ μ -

: 17/07-09-2016 (: 75 46530 - 2), 26/ 04-10-2012 (: 4 81-70)

	μ.		1501- +	(17/07-09-2016)	
μ					
15.16.01	B.01	1400 mm μ 1400 mm			
15.16.02	B.02	1400 mm 1400 mm			
15.27	B.03	μ			
15.20	B.04	17 1/2" (D450 mm) μ	08-09-01-00		
15.21	B.05	17 1/2" (D450 mm)	08-09-01-00		
√7124.2	B.06	9 5/8" 17 1/2" μ			
√7125.2	B.07	9 5/8" 17 1/2"			
15.24	B.08	μ 6mm 18" (D 450 mm),			
√7127.3	B.09	10" μ 5 mm μ			
√7128.3	B.10	μ 10" μ 5 mm			
15.12	B.11	1/2 " μ μ 1			
15.14	B.12				
15.18.02	B.13	20" μ " μ "			
15.19.02	B.14	(AIR LIFT μ μ μ)			
15.04	B.15	μ μ μ	08-09-06-00		
15.03	B.16	μ μ " μ "	08-09-06-00		

	μ.		1501- +	(17/07-09-2016)	
μ					
15.19.01	B.17	(AIR LIFT μ μ μ)			
15.18.01	B.18	20" μ " μ "			
20.02	.01	- μ	02-03-00-00		
20.05.01	.02	E μ μ μ μ	02-04-00-00		
38.03	.03		01-04-00-00		
32.01.04	.04	μ μ μ , μ μ μ μ C16/20	01-01-01-00 *	μ	01-01-01-00
			01-01-02-00		
			01-01-03-00 *	μ	01-01-03-00
			01-01-04-00 *	μ μ	01-01-04-00
			01-01-05-00		
			01-01-07-00		
38.20.02	.05	μ μ , B500C.	01-02-01-00 *	μ μ	01-02-01-00
20.10	.06	μ , μ	02-07-02-00		
46.10.04	.07	9x12x19 cm, μ μ 1 (μ) (μ)	03-02-02-00 *	μ	03-02-02-00
62.21	.08	μμ	03-08-02-00		
62.24	.09	μ	03-08-02-00		
71.22	.10	μ μ μ μ	03-03-01-00		
11.12	.11	μ μ μ	05-05-06-00		
9342	.01	μ			
\8840.5.3	.02	μ IP65			
8902.1.1	.03	, 100			
\8912.2	.04	, ,			
\9389.2	.05	() 4 x 40 , 30 mA			
8832	.06	μ , μ			
8881	.07	μ SCHUKO			

	μ.		1501- +	(17/07-09-2016)	
μ					
8801.1.4	.08	10 μ 10 250 V			
\8983.3	.09	μ led , μ			
8924	.10	25/2 μ 500 V μ			
8921.1.3	.11	μ μ μ μ 100/5 96 96 mm			
8922.1	.12	μ 0 - 500 V, μ 25/2 96 96 mm			
\8987.2	.13				
9336.1.1	.14	μ 3 1,5mm2			
9337.3.1	.15	μ 4 2,5mm2			
8773.3.5	.16	NYY μ 3 10 mm2 μ			
8915.1.2	.17	μ WL-SIEMENS μ μμ 10			
8915.1.3	.18	μ WL-SIEMENS μ μμ 16			
8915.2.4	.19	μ WL-SIEMENS μμ 20			
9347	.20	μ			
8201.1.2	.21	, μ 6 kg			

μ